

TABLE OF OFFSETS FOR KEEL BLOCKS

NO. 3 DOCKING POSITION - AFT END OF FWD BLOCK POSITIONED 39671mm (130'-1 7/8") FWD OF SRP				
KEEL BLOCK NO.	FRAME NEAREST TO AFT END OF BLOCK	DISTANCE FROM AFT END OF BLOCK TO SRP		LONGITUDINAL BEVEL IN 42"
		MM F/W/18h	HT ABOVE SHIP'S BASELINE @ AFT END OF BLOCK F/W/18h	
K16	16	39671	222	0.96
		130/1/14	0/8/12	0/0/11
K15	21	35871	158	0.96
		117/8/4	0/8/4	0/0/11
K14	24	32971	110	0.96
		109/2/1	0/4/5	0/0/11
K13	29	29259	48	0.96
		95/11/15	0/1/14	0/0/11
K12	30	27430	18	0.96
		89/11/15	0/0/11	0/0/11
K11	32	25601	-13	0.96
		83/11/15	-0/0/8	0/0/11
K10	34	23773	-44	0.96
		77/11/15	-0/1/12	0/0/11
K9	36	21944	-74	0.96
		71/11/15	-0/2/15	0/0/11
K8	37	20115	-105	0.96
		65/11/15	-0/4/2	0/0/11
K7	38	18286	-135	0.96
		59/11/15	-0/3/5	0/0/11
K6	40	16457	-165	0.96
		53/11/15	-0/6/9	0/0/11
K5	42	14629	-196	0.96
		47/11/15	-0/7/11	0/0/11
K4	44	12800	-227	0.96
		41/11/15	-0/8/15	0/0/11
K3	46	10971	-257	0.96
		35/11/15	-0/10/2	0/0/11
K2	50	6938	+1135	-2.29
		22/9/2	+3/8/11	-0/1/11
K1	55	2858	+1264	-0.63
		9/4/8	+4/1/12	-0/0/7

TABLE OF OFFSETS FOR KEEL BLOCKS

NO. 2 DOCKING POSITION - AFT END OF FWD BLOCK POSITIONED 40891mm (134'-1 7/8") FWD OF SRP				
KEEL BLOCK NO.	FRAME NEAREST TO AFT END OF BLOCK	DISTANCE FROM AFT END OF BLOCK TO SRP		LONGITUDINAL BEVEL IN 42"
		MM F/W/18h	HT ABOVE SHIP'S BASELINE @ AFT END OF BLOCK F/W/18h	
K16	15	40891	242	0.96
		134/1/14	0/9/8	0/0/11
K15	19	37091	179	0.96
		121/8/4	0/7/1	0/0/11
K14	23	34191	130	0.96
		112/2/2	0/5/2	0/0/11
K13	27	30479	88	0.96
		99/11/15	0/3/7	0/0/11
K12	29	28650	38	0.96
		93/11/15	0/1/8	0/0/11
K11	31	26821	7	0.96
		87/11/15	0/0/4	0/0/11
K10	33	24993	-23	0.96
		82/0/0	-0/0/14	0/0/11
K9	34	23164	-54	0.96
		75/11/15	-0/2/2	0/0/11
K8	36	21335	-84	0.96
		69/11/15	-0/3/5	0/0/11
K7	38	19506	-115	0.96
		63/11/15	-0/4/8	0/0/11
K6	39	17677	-145	0.96
		57/11/15	-0/5/11	0/0/11
K5	41	15849	-176	0.96
		52/0/0	-0/6/15	0/0/11
K4	43	14020	-206	0.96
		45/11/15	-0/8/2	0/0/11
K3	44	12191	-237	0.96
		39/11/15	-0/9/5	0/0/11
K2	49	8158	+1085	-5.2
		26/9/3	+3/6/11	-0/3/13
K1	53	3124	+1240	+0.34
		10/3/0	+4/0/13	+0/0/4

TABLE OF OFFSETS FOR KEEL BLOCKS

NO. 1 DOCKING POSITION - AFT END OF FWD BLOCK POSITIONED 40281mm (132'-1 7/8") FWD OF SRP				
KEEL BLOCK NO.	FRAME NEAREST TO AFT END OF BLOCK	DISTANCE FROM AFT END OF BLOCK TO SRP		LONGITUDINAL BEVEL IN 42"
		MM F/W/18h	HT ABOVE SHIP'S BASELINE @ AFT END OF BLOCK F/W/18h	
K16	16	40281	232	0.96
		132/1/14	0/9/2	0/0/11
K15	20	36481	169	0.96
		119/8/4	0/6/10	0/0/11
K14	24	33581	120	0.96
		110/2/1	0/4/12	0/0/11
K13	28	29859	58	0.96
		97/11/15	0/2/5	0/0/11
K12	30	28040	28	0.96
		91/11/15	0/1/2	0/0/11
K11	32	26211	-3	0.96
		85/11/15	-0/0/2	0/0/11
K10	33	24383	-33	0.96
		79/11/15	-0/1/5	0/0/11
K9	35	22554	-64	0.96
		73/11/15	-0/2/8	0/0/11
K8	37	20725	-94	0.96
		67/11/15	-0/3/11	0/0/11
K7	38	18896	-125	0.96
		61/11/15	-0/4/15	0/0/11
K6	40	17067	-155	0.96
		55/11/15	-0/6/2	0/0/11
K5	41	15239	-186	0.96
		49/11/15	-0/7/5	0/0/11
K4	43	13410	-216	0.96
		43/11/15	-0/8/8	0/0/11
K3	45	11581	-247	0.96
		37/11/15	-0/9/12	0/0/11
K2	49	7548	+1105	-2.41
		24/9/3	+3/7/8	-0/1/12
K1	54	2514	+1232	+0.86
		8/3/0	+4/0/8	+0/0/10